









ROHS

THIS IS A ROHS COMPLIANT COMPONENT/PRODUCT.

Reference Drawing



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 1000 MEGOHMS MIN. @ 500 VDC.
5. DIELECTRIC STRENGTH : 750 VAC 60Hz, 1MIN.
6. DIELECTRIC STRENGTH SHIELD TO LED : 1500 VAC 60Hz, 1MIN.
7. LED RATINGS: FORWARD VOLTAGE : 2.2 VOLTS TYPICAL.
REVERSE VOLTAGE : 5 VOLTS MAXIMUM.
8. OPERATING: 750 CYCLES MIN.

MECHANICAL:

1. HOUSING MATERIAL : GLASS FILLED HIGH TEMP. UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE t=0.30 mm.
UNDER PLATING: NICKEL PLATING 30~80u" OVER ALL
3. PLATING : GOLD PLATING OVER NICKEL.
4. PCB RETENTION PRE-SOLDER : 1 LB MIN.
5. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

1. STORAGE : -40°C TO +85°C.
2. OPERATION: -40°C TO +85°C.
3. IR REFLOW SOLDERING TEMPERATURE: 255°C TO 265°C (5~10 SECONDS)

MATES WITH MODULAR PLUG CONFORMING TO TIA-1096-A.

PART NUMBER: K3J1X-427-XX

01-LED1: YELLOW ,LED2:GREEN , PA9T BK

- 1-3u" 2-6u"
- 3-15u" 4-30u"
- 5-50u" 7-GOLD FLASH

LED DISPLAY		
PART NO.	LED1	LED2
K3J1X-427-01	9 YELLOW 9+ → → 10	11 GREEN 11+ → → 12

△X2	0066000	NEW DESIGN	Andy	111423
MARK	ECN-NO.	REVISION RECORD	DRAWN	DATE
UNLESS OTHERWISE SPECIFIED TOLERANCE		SCALE	CHECKED	
Dimension Range	Tolerance	1/1	APPROVED	
X.X	±0.20	UNIT	mm	
X.XX	±0.15	SIZE	A3	
X.XXX	±0.10	ANGLE	±5°	
Material/Plated/Notes		NAME		
SEE NOTE		1X1 RJ45 W/LED SMT JACK,STP		
Part No.		PART NO.	SEE NOTE	REV.
		DOC. NO.	KK3J0A427	0