



NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS.
2. CURRENT RATING: 1.5 AMP.
3. CONTACT RESISTANCE: 100 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH: 750 VAC RMS 60HZ, 1MIN.

ENVIRONMENTAL:

1. STORAGE: -40°C TO +85°C.
2. OPERATION: -40°C TO +85°C.

MECHANICAL:

1. HOUSING MATERIAL: PLASTIC UL94V-0
2. INSERT MATERIAL: PLASTIC UL94V-0
3. PCB MATERIAL: FR-4
4. SHIELD MATERIAL: SUS-301 0.20mm
4. PART NUMBER: N446X-036-0X

PART NUMBER: N446X-038-0X

- 1-3u" 2-6u" 01:6
- 3-15u" 4-30u" 02:6A
- 5-50u"

ΔX0	0069900	NEW DESIGN	LONNY	120822*
MARK	ECH-NO.	REVISION RECORD	DRAWN	DATE
		UNLESS OTHERWISE SPECIFIED TOLERANCE	CHECKED	
		SCALE		
		1:1		
		DIMENSION RANGE	TOLERANCE	APPROVED
		X..X	±0.20	mm
		X.XXX	±0.15	
		X.XXX	±0.10	
		ANGLE	A3	SHEET 1/1
		NAME	COOPER W/O LATCH FTP	
Material/Plated/Notes		PART NO.	SEE NOTE	REV. 0
SEE NOTE		DOC. NO.	NN446A038	
Tooling No.				