





RoHS

THIS IS A RoHS  
COMPLIANT  
COMPONENT/  
PRODUCT.



**NOTES:**

**ELECTRICAL:**

1. VOLTAGE RATING: 125 VAC RMS.
2. CURRENT RATING: 1.5 AMP.
3. CONTACT RESISTANCE: 100 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz,1MIN.

**ENVIRONMENTAL:**

1. STORAGE: -40°C TO +85°C.
2. OPERATION: -40°C TO +85°C.

**MECHANICAL:**

- 1.HOUSING MATERIAL:PLASTIC UL94V-0
- 2.INSERT MATERIAL:PLASTIC UL94V-0
- 3.PCB MATERIAL:FR-4
- 4.PART NUMBER: N446X-036-0X

- |        |        |        |       |
|--------|--------|--------|-------|
| 1-3u"  | 2-6u"  | 01: 6A | WHITE |
|        |        | 02: 6A | BK    |
| 3-15u" | 4-30u" | 03: 6  | WHITE |
|        |        | 04: 6  | BK    |
| 5-50u" |        |        |       |

△X0	000000	NEW DESIGN	LONNY	111622'
MARK	ECN-NO.	REVISION RECORD	DRAWN	DATE
<b>CTK</b>	UNLESS OTHERWISE SPECIFIED TOLERANCE		SCALE	CHECKED
	Dimension Range	Tolerance	1:1	APPROVED
	X.X	±0.20	UNIT	SHEET 1/1
	X.XX	±0.15	mm	
X.XXX	±0.10	SIZE		
Contact Technology Co., Ltd.		ANGLE	±5°	
Material/Plated/Notes		NAME		
SEE NOTE		COUPLER W/O LATCH		
Tooling No.	PART NO.	SEE NOTE		REV.
	DOC. NO.	NN446A036		0