



- NOTES:**
- ELECTRICAL:**
- VOLTAGE RATING
 - CURRENT RATING
 - CONTACT RESISTANCE
 - INSULATION RESISTANCE
 - DIELECTRIC STRENGTH
- MECHANICAL:**
- HOUSING MATERIAL
 - INSERT MATERIAL
 - PCB MATERIAL
 - CONTACT MATERIAL
 - IDC CONTACT MATERIAL

1. 125 VAC.
 2. 1.5 AMP.
 3. 100 MEGOHMS MAX.
 4. 1000 MEGOHMS MIN. @ 500 VDC.
 5. 750 VAC 60Hz, 1MIN.
1. PC UL94V-0
 2. GLASS FILLED POLYESTER, UL94V-0.
 3. FR-4 THICKNESS 1.6 mm.
 4. PHOSPHOR BRONZE STAMP PIN t=0.35 mm.
 5. PHOSPHOR BRONZE t=0.50 mm.
 WITH NICKEL PLATING
 #24~26 AWG.
6. WIRE ENVIRONMENTAL:
 1. STORAGE : -40°C TO +85°C.
 2. OPERATION : 0°C TO 70°C.
- PART NUMBER: N441X-036-0X
 1-3u" J
 1-3u" J
 2-6u" J
 5-50u" J

△ XI	ADD NEW PIN	LONNY	012521
△	NEW DESIGN	LONNY	011421
MARK	REVISION RECORD	DRAWN	DATE
0096900			
ECN-NO.			
TOLERANCES UNLESS OTHERWISE SPECIFIED		SCALE	
Dimension Range	Tolerance	1/1	CHECKED
XX	±0.20 UNIT		APPROVED
XXX	±0.15	mm	
XXXX	±0.10		
ANGLE	15°	A3	SHEET 1/1
NAME	180° C3 KEYSTONE		
SEE NOTE	PART NO.	REV.	
	N441X-036-0X	B	
Tooling No.	DOC. NO.	NN441A036	